



THE
ULTIMATE
OUTBOARD MOTOR

PRODUCT INFORMATION
DF140BG/115BG
DF140B/115B/100C



DF140BG/DF115BG
DF140B/DF115B/DF100C

Unit: mm

Dimension	A	B	C	D
TRANSOM:X	661	1047	1121	156
TRANSOM:L	534	920	1002	110

FEATURES	DF140BG DF115BG	DF140B DF115B	DF100C
BODY COLOR	BLACK	○	○
	WHITE	○	○
NEW SUZUKI PRECISION CONTROL (S.P.C.)	○		
NEW DYNAMIC & SMOOTH DESIGN	○	○	○
RESONATOR INTEGRATED WITH THE SILENSER	○	○	○
OFFSET DRIVE SHAFT	○	○	○
2-STAGE GEAR REDUCTION SYSTEM	○	○	○
NEW DESIGNED AIR INTAKE SYSTEM	○	○	○
SUZUKI WATER DETECTING SYSTEM	○	○	○
SUZUKI LEAN BURN CONTROL SYSTEM	○	○	○
UPGRADED COMPRESSION RATIO	○	○	○
UPGRADED VENTILATION FUNCTION	○	○	○
EASY ACCESS OIL FILTER	○	○	○
EASY ACCESS FUEL FILTER	○	○	○
OIL SPILL CATCHER	○	○	○
USABLE OIL LEVEL GAUGE	○	○	○
DUAL ENGINE FLUSH PORT	○	○	○
DIRECT IGNITION	○	○	○
SELF-ADJUSTING TIMING CHAIN	○	○	○
OPTIMAIZED O) SENSOR MOUNTING POSITION	○	○	○
LARGE CAPACITY FUEL PUMP	○	○	○
ZINC-CONTAINING RUSTPROOF COATING BOLT	○	○	○
NEW AUTOMATIC TRIM	○		
SUZUKI TROLL MODE SYSTEM*1	○	○	○
TILT LIMIT SYSTEM	○	○	○
SUZUKI ANTI-CORROSION SYSTEM	○	○	○
SDSM*2	○	○	○
KEYLESS START SYSTEM*2	○	○	○
SUZUKI EASY START SYSTEM	○	○	○
OVER REV LIMITER	○	○	○
LOW OIL PRESSURE CAUTION	○	○	○

SPECIFICATIONS	DF140BG DF115BG	DF140B DF115B	DF100C
STARTING SYSTEM	Electric		
RECOMMENDED TRANSOM HEIGHT (mm)	L:508 / X:635		
WEIGHT (kg)	DF140BG: L 188/ X 192 DF115BG: L 190/ X 194	DF140B: L 186/X 190 DF115B/DF100C: L 188/X 192	
VALVE TRAIN	DOHC 16-Valve		
FUEL DELIVERY SYSTEM	Multi-Point Sequential Electric Fuel Injection		
NO. OF CYLINDERS	4		
DISPLACEMENT (cm ³)	2,045		
MAXIMUM OUTPUT (kw)	DF140BG&B: 103 DF115BG&B: 84.6 DF100C: 73.6		
COMPRESSION RATIO	10.6		
BORE x STROKE (mm)	86 X 88		
OPERATION RANGE (rpm)	DF140BG&B: 5,700-6,300 DF115BG&B: 5,000-6,000 DF100C: 5,000-6,000		
STEERING	Remote		
OIL PAN CAPACITY (L)	5.5		
ALTERNATOR	12V 40A*		
TRIM TYPE	Power Trim and Tilt		
ENGINE MOUNTING	Shear Mount		
GEAR RATIO	2.59 : 1		
CONTROL SYSTEM	Digital	Mechanical	
RECOMMENDED FUEL	RON91,AKI87		
PROPELLER SELECTION (PITCH)	15"-25"(RR) 17"-23"(CR)		

○

○